

For installation of billet grilles that require cutting of the stock shell, proper tools, knowledge and skill are needed. Carriage Works is not responsible for care & accuracy of the installation, only for Fit & Finish of its products. Use a qualified installer or contact original vendor for references to complete all instructions.



1997-98 Ford Sport Bumper Grille
40501 / 40502 / 40503
40511 / 40512 / 40513

Step 1: Bolt steel brackets supplied to tabs on back of bumper grille.

Step 2: Center bumper grille over opening in bumper from back, position bracket towards lip on back of bumper

Step 3: Bolt in place with 1/4-20 x 3/4" bolts provided.

Note: Please adjust horizontal blades if irregular. This is the result of shipping and handling outside of Carriage Works control.

For installation of billet grilles that require cutting of the stock shell, proper tools, knowledge and skill are needed. Carriage Works is not responsible for care & accuracy of the installation, only for Fit & Finish of its products. Use a qualified installer or contact original vendor for references to complete all instructions.



1997-98 Ford Sport Bumper Grille
40501 / 40502 / 40503
40511 / 40512 / 40513

Step 1: Bolt steel brackets supplied to tabs on back of bumper grille.

Step 2: Center bumper grille over opening in bumper from back, position bracket towards lip on back of bumper

Step 3: Bolt in place with 1/4-20 x 3/4" bolts provided.

Note: Please adjust horizontal blades if irregular. This is the result of shipping and handling outside of Carriage Works control.